

# TIMBERLANE

## ENDURIAN<sup>®</sup>

### *Technical Specifications*



**1-800-250-2221 • [Timberlane.com](http://Timberlane.com)**

Timberlane Inc. • 150 Domorah Drive, Montgomeryville, PA 18936

# TIMBERLANE ENDURIAN®

*Exclusive PVC Shutter Material*



Timberlane Endurian® Shutters can be milled to create a wide variety of profiles, including panels, louvers, and more. Our proprietary synthetic blend can be modified in almost every fashion that our Premium Wood line can, while boasting long-lasting durability. Your Timberlane Expert will be happy to assist you with all of your selections, from color to shape to size, and more! Customize your Endurian Shutters to get the perfect design for your home.

## **ENDURIAN® CUSTOMIZATION OPTIONS**

STYLES: Panel, Operable Louver, Fixed Louver,  
Board & Batten and Mission

CONFIGURATIONS: Singular, 50/50, 40/60, 60/40, 33/33/33,  
20/40/40, 40/20/40, 25/25/25/25 and Custom

SIZES: Framed Shutter Thickness: 1 5/16"  
Width: 10.5" - 36"  
Length: 30" - 82"

FINISHES: Premium Paint

HARDWARE: Heavy and Standard Duty

## TIMBERLANE'S 4 ENDURIAN® SHUTTER STYLES



PANEL



LOUVER



BOARD & BATTEN



MISSION

## Panel & Mission Style Specifications

SPECIFICATION	VALUE
Materials	Proprietary blend of synthetic materials
Configurations	8 Standard or custom
Framed Shutter Thickness	1 5/16" or custom
Minimum Shutter Width	10.5"
Maximum Shutter Width	36"
Minimum Shutter Height	18"
Maximum Shutter Height	82"
Size Increments	1/8"
Stile Width	2 1/2" or custom
Top Rail Width	2 1/2" or custom
Mid Rail Width	2 1/2" or custom
Bottom Rail Width	4" +/- or custom
Panel Thickness	3/4" & 5/8" (flat panels)
Custom Rail Placement	Available
Primer	Water-based, pigmented acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors and custom color-matching
Finishes	Painted (satin)
Capping	Aluminum (painted) or copper upgrade (unfinished)

## Louver Specifications

SPECIFICATION	VALUE
Materials	Proprietary blend of synthetic materials
Configurations	8 Standard or custom
Shutter Thickness	1 5/16" or custom
Minimum Shutter Width	10.5"
Maximum Shutter Width	36"
Minimum Shutter Height	18"
Maximum Shutter Height	82"
Size Increments	1/8"
Stile Width	2 1/2" or custom
Top Rail Width	2 1/2" or custom
Mid Rail Width	2 1/2" or custom (SW1 profile 4 1/4")
Bottom Rail Width	4" +/- or custom
Louver Type	Varies by style or custom
Louver Pitch	Varies by style or custom
Louver Spacing	Varies by style or custom
Louver Width	Varies by style or custom
Louver Thickness	3/8"
Louver Direction	Traditional or reverse
Custom Rail Placement	Available
Primer	Water-based, pigmented acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors and custom color-matching
Finishes	Painted (satin)
Capping	Aluminum (painted) or copper upgrade (unfinished)

## Board & Batten Specifications

SPECIFICATION	VALUE
Materials	Proprietary blend of synthetic materials
Configurations	Various styles available (Closed boards only)
Shutter Thickness	Board - 1" Batten - 1"
Minimum Shutter Width	10.5"
Maximum Shutter Width	36"
Minimum Shutter Height	18"
Maximum Shutter Height	82"
Size Increments	1/8"
Individual Board or Batten Widths and Quantities	Customizable
Custom Batten Placement	Available
Primer	Water-based, pigmented acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors and custom color-matching
Finishes	Painted (satin)
Capping	Aluminum (painted) or copper upgrade (unfinished)

## Bermuda Specifications

SPECIFICATION	VALUE
Style not available	