

# TIMBERLANE FUNDAMENTALS

*Technical Specifications*



**1-800-250-2221 • [Timberlane.com](https://www.timberlane.com)**

Timberlane Inc. • 150 Domorah Drive, Montgomeryville, PA 18936

# TIMBERLANE FUNDAMENTALS

*The “Better-Than-Basic” Shutter*



When you're looking for a “better-than-basic” shutter that will still give your home a sophisticated look, our Fundamentals Shutters are the ideal solution. They are custom built to 1/2” specifications and are typically delivered primed or painted in your choice of paint color. Component-built for greater stability, these solid composite shutters offer a more substantial look and feel than vinyl shutters found in stores, and can be installed for function or simply for decoration.

## FUNDAMENTALS CUSTOMIZATION OPTIONS

STYLES: Panel, Faux Louvers, or Board & Batten

CONFIGURATIONS: Singular, 50/50, 40/60, 60/40, 33/33/33,  
20/40/40, 40/20/40, 25/25/25/25

FINISHES: Primed or Premium Paint

HARDWARE: Limited Selection

## TIMBERLANE'S 3 FUNDAMENTALS SHUTTER STYLES



PANEL



LOUVER



BOARD & BATTEN

## Panel Specifications

SPECIFICATION	VALUE
Materials	High-performance exterior wood composite
Configurations	8 Standard
Shutter Thickness	1 ¼"
Minimum Shutter Width	12"
Maximum Shutter Width	24"
Minimum Shutter Height	30"
Maximum Shutter Height	96"
Size Increments	½"
Stile Width	2 ½"
Top Rail Width	2 ½"
Mid Rail Width	2 ½"
Bottom Rail Width	3 ½"
Panel Thickness	¾"
Primer	Water-based, pigmented acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors or custom
Finishes	Primed, factory-finished (satin)
Capping	Aluminum (unfinished or painted) or copper upgrade (unfinished)

## Louver Specifications

SPECIFICATION	VALUE
Materials	High-performance exterior wood composite
Configurations	8 Standard
Shutter Thickness	1 ¼"
Minimum Shutter Width	12"
Maximum Shutter Width	24"
Minimum Shutter Height	30"
Maximum Shutter Height	96"
Size Increments	½"
Stile Width	2 ½"
Top Rail Width	2 ½"
Mid Rail Width	2 ½"
Bottom Rail Width	3 ½" +/-
Panel Thickness	¾"
Louver Type	Faux
Louver Direction	Reverse
Primer	Water-based, pigmented acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors or custom
Finishes	Primed, factory-finished (satin)
Capping	Aluminum (unfinished or painted) or copper upgrade (unfinished)

## Board & Batten Specifications

SPECIFICATION	VALUE
Materials	High-performance exterior wood composite
Configurations	1 Style available
Shutter Thickness	Board - 1" Batten - 1"
Minimum Shutter Width	12"
Maximum Shutter Width	24"
Minimum Shutter Height	30"
Maximum Shutter Height	96"
Size Increments	½"
Individual Board Widths and Quantities	Variable
Batten Placement	Standard
Primer	Water-based, pigmented acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors or custom
Finishes	Primed, factory-finished (satin)
Capping	Aluminum (unfinished or painted) or copper upgrade (unfinished)

## Bermuda Specifications

SPECIFICATION	VALUE
Style not available	