

TIMBERLANE PREMIUM WOOD

Technical Specifications



1-800-250-2221 • Timberlane.com

Timberlane Inc. • 150 Domorah Drive, Montgomeryville, PA 18936

TIMBERLANE PREMIUM WOOD

Traditional Beauty, Built to Last



Timberlane Premium Wood Shutters can be constructed in nearly every configuration imaginable, including combinations of both panel and louver profiles. The various profile options shown here illustrate the wide range of panel and louver designs available for creating your masterpiece. Premium Wood Shutters are available in 24 Premium Paint colors or can be custom-matched to your preferred color. You also have the option to stain and clear-coat your Premium Wood Shutters for an elegant, natural look.

PREMIUM WOOD CUSTOMIZATION OPTIONS

STYLES: Panel, Operable Louver, Fixed Louver,
Board & Batten, Bermuda (Bahama) and Mission

CONFIGURATIONS: Singular, 50/50, 40/60, 60/40, 33/33/33,
20/40/40, 40/20/40, 25/25/25/25 and Custom

SIZES: Framed Shutter Thickness: 1⁵/₁₆" • Overall Board & Batten Thickness: 2"
Width: 10.5" - 36"
Length: 18" - 116"

FINISHES: Unfinished, Primed, Premium Paint, Clear-Coated,
Stained, and Semi-Transparent

HARDWARE: All

TIMBERLANE'S 5 PREMIUM WOOD SHUTTER STYLES



PANEL



LOUVER



BOARD & BATTEN



BERMUDA



MISSION

Panel & Mission Style Specifications	
SPECIFICATION	VALUE
Materials	Select Wood Species
Configurations	8 Standard or custom
Framed Shutter Thickness	1 5/16" or custom
Minimum Shutter Width	10.5"
Maximum Shutter Width	36"
Minimum Shutter Height	18"
Maximum Shutter Height	116"
Size Increments	1/8"
Stile Width	2 1/2" or custom
Top Rail Width	2 1/2" or custom
Mid Rail Width	2 1/2" or custom
Bottom Rail Width	4" or custom
Panel Thickness	5/8", 3/4", 7/8"
Custom Rail Placement	Available
Primer	Tannin-blocking, water-based acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors and custom color-matching
Finishes	Unfinished, primed, painted, clear coat, stained* and semi-transparent*
Capping	Aluminum (unfinished or painted) or copper upgrade (unfinished)

*Stained and semi-transparent finishes are available for select wood species.

Louver Specifications	
SPECIFICATION	VALUE
Materials	Select Wood Species
Configurations	8 Standard or custom
Shutter Thickness	1 5/16" or custom
Minimum Shutter Width	10.5"
Maximum Shutter Width	36"
Minimum Shutter Height	18"
Maximum Shutter Height	116"
Size Increments	1/8"
Stile Width	2 1/2" or custom
Top Rail Width	2 1/2" or custom
Mid Rail Width	2 1/2" or custom
Bottom Rail Width	4" +/- or custom
Louver Type	Varies by style or custom
Louver Pitch	Varies by style or custom
Louver Spacing	Varies by style or custom
Louver Width	Varies by style or custom
Louver Thickness	3/8" or custom (NE1 profile 1/4")
Louver Direction	Traditional or reverse
Custom Rail Placement	Available
Primer	Tannin-blocking, water-based acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors and custom color-matching
Finishes	Unfinished, primed, painted, clear coat, stained* and semi-transparent*
Capping	Aluminum (unfinished or painted) or copper upgrade (unfinished)

Board & Batten Specifications	
SPECIFICATION	VALUE
Materials	Select Wood Species
Configurations	Various styles available
Shutter Thickness	Board - 1" Batten - 1"
Minimum Shutter Width	10.5"
Maximum Shutter Width	36"
Minimum Shutter Height	18"
Maximum Shutter Height	116"
Size Increments	1/8"
Individual Board Widths and Quantities	Customizable
Custom Rail Placement	N/A
Primer	Tannin-blocking, water-based acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors and custom color-matching
Finishes	Unfinished, primed, painted, clear coat, stained* and semi-transparent*
Capping	Aluminum (unfinished or painted) or copper upgrade (unfinished)

*Stained and semi-transparent finishes are available for select wood species.

Bermuda Specifications	
SPECIFICATION	VALUE
Materials	Select Wood Species
Configurations	Mid stile/mid rail or both
Shutter Thickness	1 5/16" or custom
Minimum Shutter Width	18"
Maximum Shutter Width	144"
Minimum Shutter Height	18"
Maximum Shutter Height	116"
Size Increments	1/8"
Stile Width	2 1/2" or custom
Top Rail Width	2 1/2" or custom
Mid Rail Width	2 1/2" or custom (SW1 profile 4 1/4")
Bottom Rail Width	4" +/- or custom
Louver Type	Varies by style or custom
Louver Pitch	Varies by style or custom
Louver Spacing	Varies by style or custom
Louver Width	Varies by style or custom
Louver Thickness	3/8" or custom
Louver Direction	Reverse
Custom Rail Placement	Available
Primer	Tannin-blocking, water-based acrylic
Paint	Flexible, water-based acrylic with UV protection & reflective additives
Colors	24 Standard colors and custom color-matching
Finishes	Unfinished, primed, painted, clear coat, stained* and semi-transparent*
Capping	Not available